# **Product datasheet**

Specifications





# Switched socket, S-Classic, 13A, 250V, 1 gang

E15

#### Main

Range	S-Classic
Product Or Component Type	Socket-outlet with switch
Device Application	Power supply
Outlet Poles Configuration	2P + E
Rated Current	13 A at 250 V AC 50/60 Hz
Quantity Per Set	Set of 1

#### Complementary

	<u>,</u>
Number Of Gangs	1 gang
Device Mounting	Flush Surface
Material	PC (polycarbonate)
Embedding Depth	13.8 mm
Height	87 mm
Width	87 mm
Depth	29.3 mm

#### Environment

Ambient Air Temperature For Operation	-540 °C
Relative Humidity	095 %
Standards	MS 589-2 SS 145-2 BS 1363-2

## **Packing Units**

—	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.7 cm
Package 1 Width	8.7 cm
Package 1 Length	2.93 cm
Package 1 Weight	0.001 g

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations