



# S-Classic - 250V 20AX - 2-pole switch with neon - 1 gang - white

E32D20NA\_WE

#### Main

| Range                     | S-Classic |
|---------------------------|-----------|
| Product Or Component Type | Switch    |
| Device Application        | Control   |
| Switch Application        | Lighting  |
| Quantity Per Set          | Set of 1  |

### Complementary

| Control Type    | Rocker  |  |
|-----------------|---|--|
| Actuator        | Rocker  |  |
| Switch Function | 2-pole  |  |
| Number Of Gangs | 1 gang  |  |
| Pilot Light     | Red neon indicator  |  |
| Device Mounting | Flush<br>Surface  |  |
| Rated Current   | 20 AX at 250 V AC   |  |
| Material        | Plate: PC (polycarbonate), white<br>Dolly: PC (polycarbonate), white<br>Base: PA66, black |  |
| Embedding Depth | 18.7 mm   |  |
| Height          | 87 mm   |  |
| Width           | 87 mm   |  |
| Depth           | 35.1 mm   |  |

#### **Environment**

| Ambient Air Temperature For Operation | -540 °C  |
|---------------------------------------|--|
| Relative Humidity                     | 095 %  |
| Standards                             | GB 16915.1<br>IEC 60669-1<br>SS 227-1<br>MS IEC 60669-1<br>BS EN 60669-1 |

## **Packing Units**

| Unit Type Of Package 1       | PCE |
|------------------------------|-----|
| Number Of Units In Package 1 | 1   |

| Package 1 Height             | 22 cm   |
|------------------------------|---------|
| Package 1 Width              | 32.5 cm |
| Package 1 Length             | 49.5 cm |
| Package 1 Weight             | 90.5 g  |
| Unit Type Of Package 2       | BB1     |
| Number Of Units In Package 2 | 10      |
| Package 2 Height             | 15 cm   |
| Package 2 Width              | 19 cm   |
| Package 2 Length             | 10 cm   |
| Package 2 Weight             | 905 g   |
| Unit Type Of Package 3       | CAR     |
| Number Of Units In Package 3 | 100     |
| Package 3 Height             | 22 cm   |
| Package 3 Width              | 32.5 cm |
| Package 3 Length             | 49.5 cm |
| Package 3 Weight             | 9050 g  |



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

| <b>⊘</b> | Reach Free Of Svhc         |     |
|----------|----------------------------|-----|
| <b>Ø</b> | Toxic Heavy Metal Free     |     |
| <b>⊘</b> | Mercury Free               |     |
| <b>⊘</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant EU RoHS Declaration   |
| China Rohs Regulation    | China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |