

Product datasheet

Specifications



Actassi - Unitube Light Armoured Cable MM, 12 Core, 50um



ACTUDUTLA12MM5T

! Discontinued on: 15 Jun 2023

! Discontinued

Main

Range	Actassi
Product	Fibre optic cable multi mode
Device Application	Communication
Cable Packaging	Reel

Complementary

Maximum Attenuation	3.5 dB / 1 km at 850 nm 1.5 dB / 1 km at 1300 nm
Fibre Performance	OM3 50/125 µm
Optic Fibre Type	Loose tube diameter: 250 µm
Type Of Cable	Unitube light armoured
Numerical Aperture	0.2 +/- 0.015
Number Of Optic Fibre	12
Bending Radius	10 x overall diameter long term 20 x overall diameter short term
Pulling Force	1500 N installed 600 N operation
Colour	Sheath: black
Type Of Installation	Outdoor
Cabling Installation System	Cable duct
Diameter	10.6 mm cable +/- 0.2 mm 0.8 mm cable +/- 0.2 mm
Cable Weight	82 kg / 1000 m
Targeted Region	Asia Pacific.

Environment

Ambient Air Temperature For Operation	-40...70 °C
Environmental Characteristic	UV and water resistant: HDPE (high-density polyethylene) Rodent retardant: PSP (polyethylene steel polyethylene)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Package 1 Height	90 cm
Package 1 Width	55 cm
Package 1 Length	80 cm
Package 1 Weight	135 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

No need of specific recycling operations