

Product data sheet

Specifications

Actassi - patch panel - category 6A - 10G - FTP - 24-port - loaded



ACTPP6ATGS24NSS

⚠ Discontinued on: Jun 15, 2023

⚠ Discontinued

Main

Range Of Product	Actassi
Product Or Component Type	Patch panel
Device Presentation	Loaded
Provided Equipment	With RJ45 connectors

Complementary

[In] Rated Current	1.5 A
Number Of Port	24 port of FTP
Product Compatibility	standard 19" cabinet/rack
Communication Network Category	6 _A
Contact Resistance	20 μOhm
Insulation Resistance	>= 10 MOhm
Minimum Number Of Matings	750 cycles
Number Of Rack Unit	1U

Environment

Ambient Air Temperature For Operation	-10...50 °C
Ambient Air Temperature For Storage	-20...60 °C
Relative Humidity	0...93 %
Standards	TIA/EIA-568-B

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.5 cm
Package 1 Width	5.2 cm
Package 1 Length	49.7 cm
Package 1 Weight	837.0 g

Contractual warranty

Warranty	18 months
----------	-----------

List Price displayed is VAT EXCLUSIVE.

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

Eu Rohs Directive

Under investigation

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations