Product datasheet

Specifications



Actassi - patch panel - category 6A - 10G - FTP - 24-port - unloaded



ACTPPS24NSU

Main

Range Of Product	Actassi
Product Or Component Type	Patch panel
Device Presentation	Empty
Provided Equipment	Without RJ45 connectors

Complementary

[In] Rated Current	1.5 A
Number Of Port	24 port of FTP
Product Compatibility	standard 19" cabinet/rack
Communication Network Category	6 _A
Contact Resistance	20 μOhm
Insulation Resistance	>= 10 MOhm
Minimum Number Of Matings	750 cycles
Number Of Rack Unit	1U
Type Of Connector	S-110 keystone

Environment

Ambient Air Temperature For Operation	-1050 °C
Ambient Air Temperature For Storage	-2060 °C
Relative Humidity	093 %
Standards	TIA/EIA-568-B

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	12.5 cm
Package 1 Length	50 cm
Package 1 Weight	864 a

Contractual warranty

Warranty	18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations