

Product datasheet

Specifications



Actassi - cable - category 5e - 4 pair - UTP - 305m - blue - CM



ACT4P5EUCM3RBBU

! Discontinued on: 15 Jun 2023

! Discontinued

Main

Range	Actassi
Product Or Component Type	Copper cable
Colour Tint	Blue
Cable Shielding Type	U/UTP

Complementary

Type Of Cable	4 pair cables
Communication Network Category	5e
Minimum Return Loss	Guaranteed: 19.4 dB at 0.772 MHz Guaranteed: 20 dB at 1 MHz Guaranteed: 23 dB at 4 MHz Guaranteed: 24.5 dB at 8 MHz Guaranteed: 25 dB at 10 MHz Guaranteed: 25 dB at 16 MHz Guaranteed: 25 dB at 20 MHz Guaranteed: 24.3 dB at 25 MHz Guaranteed: 23.6 dB at 31.25 MHz Guaranteed: 21.5 dB at 62.5 MHz Guaranteed: 20.1 dB at 100 MHz
Attenuation	Guaranteed: 1.8 dB @ 0.772 MHz per 100 m cable Guaranteed: 2 dB @ 1 MHz per 100 m cable Guaranteed: 4.1 dB @ 4 MHz per 100 m cable Guaranteed: 5.8 dB @ 8 MHz per 100 m cable Guaranteed: 6.5 dB @ 10 MHz per 100 m cable Guaranteed: 8.2 dB @ 16 MHz per 100 m cable Guaranteed: 9.3 dB @ 20 MHz per 100 m cable Guaranteed: 10.4 dB @ 25 MHz per 100 m cable Guaranteed: 11.7 dB @ 31.25 MHz per 100 m cable Guaranteed: 17 dB @ 62.5 MHz per 100 m cable Guaranteed: 22 dB @ 100 MHz per 100 m cable
Power Sum Near-End Crosstalk [Psn _{ext}]	Guaranteed: 64 dB at 0.772 MHz Guaranteed: 62.3 dB at 1 MHz Guaranteed: 53.3 dB at 4 MHz Guaranteed: 48.8 dB at 8 MHz Guaranteed: 47.3 dB at 10 MHz Guaranteed: 44.3 dB at 16 MHz Guaranteed: 42.8 dB at 20 MHz Guaranteed: 41.3 dB at 25 MHz Guaranteed: 39.9 dB at 31.25 MHz Guaranteed: 35.4 dB at 62.5 MHz Guaranteed: 32.3 dB at 100 MHz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Near End Crosstalk [Next]	Guaranteed: 67 dB at 0.772 MHz
	Guaranteed: 65.3 dB at 1 MHz
	Guaranteed: 56.3 dB at 4 MHz
	Guaranteed: 51.8 dB at 8 MHz
	Guaranteed: 50.3 dB at 10 MHz
	Guaranteed: 47.3 dB at 16 MHz
	Guaranteed: 45.8 dB at 20 MHz
	Guaranteed: 44.3 dB at 25 MHz
	Guaranteed: 42.9 dB at 31.25 MHz
	Guaranteed: 38.4 dB at 62.5 MHz
Guaranteed: 35.3 dB at 100 MHz	

Input Impedance	100 Ohm (+/- 6) at 1...100 MHz
------------------------	--------------------------------

Maximum Loop Resistance	93.8 Ohm
--------------------------------	----------

Capacitance Unbalance	330 pF / 100 m
------------------------------	----------------

Maximum Resistance Unbalance	5 %
-------------------------------------	-----

Wire Insulation Material	PE
---------------------------------	----

Conductor Material	Solid bare copper
---------------------------	-------------------

Awg Gauge	AWG 24
------------------	--------

Cable Outer Diameter	4.9 mm
-----------------------------	--------

Cable Length	305 m
---------------------	-------

Environment

Ambient Air Temperature For Operation	75 °C
--	-------

Product Certifications	UL
-------------------------------	----

Flame Retardance	CM
-------------------------	----

Standards	ANSI/TIA/EIA-568-B UL 444 ISO/IEC 11801
------------------	---

Packing Units

Unit Type Of Package 1	PCE
-------------------------------	-----

Number Of Units In Package 1	1
-------------------------------------	---

Package 1 Height	21.0 cm
-------------------------	---------

Package 1 Width	35.0 cm
------------------------	---------

Package 1 Length	35.0 cm
-------------------------	---------

Package 1 Weight	11.0 kg
-------------------------	---------

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations