


# Product datasheet

Specifications



## Actassi FL-C Fibre Cable OM4 50/125µm Loose Tube 6 fibres 2100m Euroclass D

VDICD52406L

### Main

Range	Actassi
Product	Fibre optic cable multi mode
Device Application	Communication
Cable Packaging	Drum of 2100 m

### Complementary

Maximum Attenuation	0.6 dB at 1300 nm 2.4 dB at 850 nm
Bandwidth	LED: 500 MHz.km at 1300 nm LED: 3500 MHz.km at 850 nm
Fibre Performance	OM4 50/125 µm
Optic Fibre Type	Loose tube diameter: 250 µm
Type Of Cable	Non armoured
Number Of Optic Fibre	6
Bending Radius	10 x overall diameter long term 20 x overall diameter short term
Pulling Force	1500 N
Crush Resistance	20000 N/m
Refractive Index Group	1.482 at 850 nm 1.477 at 1300 nm
Colour	External sheath: green, RAL 6016
Type Of Installation	Indoor/outdoor
Cabling Installation System	Cable duct
Calorific Value	0.542 MJ
Diameter	7.5 mm
Cable Weight	55 kg / 1000 m
Targeted Region	Europe

### Environment

Ambient Air Temperature For Operation	-30...70 °C
Ambient Air Temperature For Installation	-15...40 °C
Ambient Air Temperature For Storage	-40...60 °C
Euroclass Level	Dca s2 d2 a2

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Flame Retardance</b>	LSZH
<b>Environmental Characteristic</b>	Rodent retardant: glass yarn Water resistant (longitudinally): gel Water resistant (longitudinally): swellable yarn UV resistant:
<b>Standard</b>	Cable specification conforming to IEC 60794-2 Cable test procedure conforming to IEC 60794-1-2 Fibre colour coding conforming to TIA/EIA-598-A Fibre performance conforming to IEC 60793-2-10 Type A1a.3 Fibre performance conforming to TIA-492AAAD OM4 Flame retardance conforming to IEC 60332-1 conforming to IEC 60754-2 Fibre performance conforming to ITU G.651.1 conforming to ISO/IEC 11801 Fibre performance conforming to EN 50173-1 conforming to EN 50399

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	49.0 cm
<b>Package 1 Width</b>	75.0 cm
<b>Package 1 Length</b>	75.0 cm
<b>Package 1 Weight</b>	10.0 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

No need of specific recycling operations