

Product datasheet

Specifications



Fibre optic patch cord, Actassi, OM3, LC-LC, duplex, LSZH, 3 m

ACTFP2L1M35M30

Main

| | |
|---------------------------|--|
| Range | Actassi |
| Product Or Component Type | Multimode fibre optic patchcord |
| Colour | Sheath: aqua LC duplex housing: aqua LC duplex boot: white LC duplex clip: aqua |
| Cable Packaging | Roll of 3 m |
| Type Of Packing | plastic bag |

Complementary

| | |
|------------------------|--|
| Maximum Attenuation | 3.5 dB / 1 km at 850 nm 1.5 dB / 1 km at 1300 nm |
| Bending Radius | 32 mm dynamic 16 mm static |
| Maximum Insertion Loss | 0.2 dB LC |
| Minimum Return Loss | 30 dB LC |
| Fibre Performance | OM3 50/125 µm |
| Optic Fiber Diameter | 600 µm |
| Termination 1 | LC |
| Termination 2 | LC |
| Sheath Type | Zip 2 x 1.6 mm |
| Condition Of Use | Patching |
| Exchange Mode | Duplex |
| Mode Of Transmission | Multi mode |
| Number Of Optic Fibre | 2 |
| Width | 3.4 mm |
| Height | 1.6 mm |
| Material | Ceramic: LC connector ferrule Thermoplastic: LC duplex housing TPE (thermoplastic elastomer): boot |
| Cable Length | 3 m |
| Targeted Region | Europe Asia Pacific. |

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|---|--|
| Ambient Air Temperature For Operation | -20...60 °C |
| Ambient Air Temperature For Installation | -20...60 °C |
| Ambient Air Temperature For Storage | -20...60 °C |
| Standards | Fibre performance: ITU G.651 Flame retardance: IEC 60332-1 IEC 60754-1 IEC 60754-2 IEC 61034 Fibre performance: IEC 60793-2-10 Type A1a.2 LC connector: TIA/EIA-604-10 A LC connector: IEC 61754-20 Ed.2 Fibre performance: ISO/IEC 11801:2011 Ed.2.2 OM3 Fire retardance: IEC 60332-3C Fibre performance: TIA/EIA-568-C.3 Flame retardance: UL 94 V0 |

Packing Units

| | |
|-------------------------------------|------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 1.0 cm |
| Package 1 Width | 16.0 cm |
| Package 1 Length | 16.0 cm |
| Package 1 Weight | 39.77 g |
| Unit Type Of Package 2 | CAR |
| Number Of Units In Package 2 | 180 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 39.7 cm |
| Package 2 Length | 59.8 cm |
| Package 2 Weight | 10.539 kg |
| Unit Type Of Package 3 | P12 |
| Number Of Units In Package 3 | 2160 |
| Package 3 Height | 102.0 cm |
| Package 3 Width | 80.0 cm |
| Package 3 Length | 120.0 cm |
| Package 3 Weight | 144.463 kg |

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Circularity Profile No need of specific recycling operations
