

Product datasheet

Specifications



AvatarOn, 2 switched socket, 3P, 13 A, 250 V, White

E83T25_WE_G12

Main

Product Or Component Type	Switched socket
Device Application	Power supply
Device Presentation	Complete product
Outlet Poles Configuration	3P with shutter
Type Of Packing	Flow-pack

Complementary

Rated Current	13 A socket-outlet
[Ue] Rated Operational Voltage	250 V AC 50/60 Hz
Socket Number	2
Outlet Standard Description	With earthing contact
Outlet Standard	British BS 1363A
Number Of Gangs	2 gangs
Service Life In Cycles	20000 cycles
Electrical Durability	5000 cycles
Connections - Terminals	Screw terminal
Material	Polycarbonate: grid plate Polycarbonate: surround
Surface Finish	Glossy
Surface Treatment	Painted mechanism cover
Device Mounting	Surface
Fixing Mode	Screw
Height	86 mm
Width	146 mm
Depth	31.7 mm

Environment

Ip Degree Of Protection	IP20
Ambient Air Temperature For Operation	-5...45 °C
Ambient Air Temperature For Storage	-5...60 °C
Relative Humidity	0...95 %

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Standards	BS 1363 MS 589 SS 145
------------------	-----------------------------

Product Certifications	SIRIM
-------------------------------	-------

Packing Units

Unit Type Of Package 1	PCE
-------------------------------	-----

Number Of Units In Package 1	1
-------------------------------------	---

Package 1 Height	3.2 cm
-------------------------	--------

Package 1 Width	8.6 cm
------------------------	--------

Package 1 Length	14.6 cm
-------------------------	---------

Package 1 Weight	151.0 g
-------------------------	---------

Unit Type Of Package 2	CAR
-------------------------------	-----

Number Of Units In Package 2	7
-------------------------------------	---

Package 2 Height	9.5 cm
-------------------------	--------

Package 2 Width	19.0 cm
------------------------	---------

Package 2 Length	19.5 cm
-------------------------	---------

Package 2 Weight	1.104 kg
-------------------------	----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations