Product datasheet

Specifications





AvatarOn, fused connection, 25A, 250V, White

E8331TB_WE

Price: 71.83 USD

Main

Range	AvatarOn
Device Application	Connection unit
Product Or Component Type	Connection unit
Quantity Per Set	Set of 1
Product Brand	Schneider Electric

Complementary

Device PresentationComplete productColour TintWhiteNumber Of Gangs1 gangSurface FinishGlossyMaterialPC (polycarbonate)Mounting SupportWall mountedFixing ModeBy screwsRated Current25 A at 250 V AC 5060 HzConnections - TerminalsPillar terminalsHeight86 mmWidth86 mmDepth38 mmIp Degree Of ProtectionIP20		
Number Of Gangs 1 gang Surface Finish Glossy Material PC (polycarbonate) Mounting Support Wall mounted Fixing Mode By screws Rated Current 25 A at 250 V AC 5060 Hz Connections - Terminals Pillar terminals Height 86 mm Width 86 mm Depth 38 mm	Device Presentation	Complete product
Surface Finish Glossy Material PC (polycarbonate) Mounting Support Wall mounted Fixing Mode By screws Rated Current 25 A at 250 V AC 5060 Hz Connections - Terminals Pillar terminals Height 86 mm Width 86 mm Depth 38 mm	Colour Tint	White
Material PC (polycarbonate) Mounting Support Wall mounted Fixing Mode By screws Rated Current 25 A at 250 V AC 5060 Hz Connections - Terminals Pillar terminals Height 86 mm Width 86 mm Depth 38 mm	Number Of Gangs	1 gang
Mounting Support Wall mounted Fixing Mode By screws Rated Current 25 A at 250 V AC 5060 Hz Connections - Terminals Pillar terminals Height 86 mm Width 86 mm Depth 38 mm	Surface Finish	Glossy
Fixing Mode By screws Rated Current 25 A at 250 V AC 5060 Hz Connections - Terminals Pillar terminals Height 86 mm Width 86 mm Depth 38 mm	Material	PC (polycarbonate)
Rated Current 25 A at 250 V AC 5060 Hz Connections - Terminals Pillar terminals Height 86 mm Width 86 mm Depth 38 mm	Mounting Support	Wall mounted
Connections - Terminals Pillar terminals Height 86 mm Width 86 mm Depth 38 mm	Fixing Mode	By screws
Height 86 mm Width 86 mm Depth 38 mm	Rated Current	25 A at 250 V AC 5060 Hz
Width 86 mm Depth 38 mm	Connections - Terminals	Pillar terminals
Depth 38 mm	Height	86 mm
	Width	86 mm
Ip Degree Of Protection IP20	Depth	38 mm
	Ip Degree Of Protection	IP20

Environment

Standards

BS 5733

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.7 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	162 g
Unit Type Of Package 2	CAR

Excluding VAT, FCA Jabal Ali & are subject to change - check with your local distributor.

Number Of Units In Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	9 cm
Package 2 Length	19.5 cm
Package 2 Weight	1.297 kg
Unit Type Of Package 3	PAL
Number Of Units In Package 3	1728
Package 3 Height	110 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	291.12 kg

Contractual warranty

Warranty

18 Months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Yes

Sustainable Packaging Transparency RoHS/REACh

Resource performance

Sustainable Packaging

Well-being performance

Mercury Free

Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations