

Product datasheet

Specifications



5A 250V 1 Gang 3 Round Pin Switched Socket with Neon

E8215-5N

Main

Range	Pieno
Product Or Component Type	Power socket-outlet
Switch Function	Switch
Rated Current	5 A at 250 V AC 50...60 Hz
Number Of Gangs	1 gang
Load Type	Resistive

Complementary

Wiring Device Mounting	Surface Flush
Material	Polycarbonate: surround Polycarbonate: grid plate
Clamping Connection Capacity	2 x 2.5 mm ² for solid cable(s)
Width	87 mm
Height	87 mm
Depth	26.8 mm

Environment

Ambient Air Temperature For Operation	-5...40 °C
Relative Humidity	0...95 %
Standards	BS 546

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.7 cm
Package 1 Width	8.7 cm
Package 1 Length	2.68 cm
Package 1 Weight	0.001 g

Contractual warranty

Warranty	18 months
----------	-----------

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations