


# Product datasheet

Specifications



## 16AX 250V 4 GANG 1 WAY SWITCH

KB34\_1\_WE

⚠ Discontinued on: 30 Jun 2023

⚠ Discontinued

### Main

Range	Vivace
Product Or Component Type	Switch
Device Short Name	KB34
Device Application	Lighting
Additional Switch Application	Switch
Switch Function	1-way

### Complementary

Device Presentation	Complete product
Actuator	Rocker
Number Of Gangs	4 gangs
Colour Tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Surface Finish	Glossy
Surface Treatment	Untreated
Type Of Packing	Plastic bag
Quantity Per Set	1
Projecting Depth	8 mm
Device Mounting	Flush
Mounting Support	Wall mounted
Fixing Mode	By screw M3.5
Fixing Center	120.6 mm
Embedding Depth	35 mm
Rated Current	16 AX at 250 V AC, inductive 16 AX at 250 V AC, fluorescent
[Ue] Rated Operational Voltage	250 V AC
Network Frequency	50/60 Hz
Connections - Terminals	8 pillar terminal
Terminal Identifier	COM L1

<b>Tightening Torque</b>	0.4 N.m
<b>Clamping Connection Capacity</b>	<= 2.5 mm <sup>2</sup> for rigid or stranded cable(s)
<b>Wire Stripping Length</b>	12 mm
<b>Width</b>	146 mm
<b>Height</b>	86 mm
<b>Depth</b>	36 mm

## Environment

<b>Standards</b>	IEC 60669-1 SS 227 MS IEC 60669-1
<b>Ambient Air Temperature For Operation</b>	-5...40 °C
<b>Relative Humidity</b>	0...95 %
<b>Operating Altitude</b>	0...2000 m
<b>Environmental Characteristic</b>	Indoor use
<b>Ip Degree Of Protection</b>	IP20

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	3.1 cm
<b>Package 1 Width</b>	8.6 cm
<b>Package 1 Length</b>	14.6 cm
<b>Package 1 Weight</b>	136 g
<b>Unit Type Of Package 2</b>	CAR
<b>Number Of Units In Package 2</b>	50
<b>Package 2 Height</b>	21 cm
<b>Package 2 Width</b>	31.5 cm
<b>Package 2 Length</b>	50 cm
<b>Package 2 Weight</b>	7500 g
<b>Unit Type Of Package 3</b>	P12
<b>Number Of Units In Package 3</b>	1000
<b>Package 3 Height</b>	120 cm
<b>Package 3 Width</b>	80 cm
<b>Package 3 Length</b>	120 cm
<b>Package 3 Weight</b>	222000 g

## Sustainability


**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

 Mercury Free

---

 Rohs Exemption Information [Yes](#)

---

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Compliant with Exemptions

---

**China Rohs Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

---