

# Product datasheet

Specifications



## 5A 250V 1 Gang Switched Socket

KB15\_5

⚠ Discontinued on: 21-Feb-2017

⚠ End-of-service on: 13-Mar-2017

⚠ Discontinued

### Main

Range	Vivace
Product Or Component Type	Switched socket
Device Short Name	KB15
Device Presentation	Complete product

### Complementary

Outlet Poles Configuration	2P + E
Number Of Gangs	1 gang
Colour Tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting Depth	8 mm
Device Mounting	Flush
Mounting Support	Wall mounted
Fixing Mode	By screw M3.5
Fixing Center	60.3 mm
Embedding Depth	35 mm
Rated Current	5 A at 250 V AC, resistive 5 A at 250 V AC, inductive
Network Frequency	50 Hz
Contacts Material	Brass and phosphor bronze
Connections - Terminals	Pillar terminal
Terminal Identifier	N Earth L
Tightening Torque	0.4 N.m
Clamping Connection Capacity	<= 1.5 mm <sup>2</sup>
Width	86 mm
Height	86 mm

### Environment

Standards	BS 546
-----------	--------

---

Ambient Air Temperature For Operation	-5...40 °C
Relative Humidity	0...95 %
Environmental Characteristic	Indoor use

---

## Contractual warranty

---

Warranty	18 months
----------	-----------