

panel GLASS TOUCH PANELS for hotels - modbus - 9 buttons - sample order

LSSMBU09NS

Main

Product name	Glass Touch Panels Configurable touchscreen panel	
product type		
Device application	Remote control	
	Energy efficiency	
	Hotel	
	Monitoring	
	Bell switch	
	Ventilation	
	Lighting	
color buttons display options	Champagne gold	
	Silver	
	Black	
	White	
Colour tint	Panel: black	
	Panel: white	
	Panel: silver	
	Panel: champagne gold	
	Button: white	
	Button: amber	
	Button: blue	
	Button: light green	
	Button: red	
	Button: grey	
Module configuration	Configurated with the Glass Touch Panel Design tool	

Complementary

•		
Control button type	9 configurable touch button	
Local signalling	configurable	
[Us] rated supply voltage	24 V DC	
Current consumption	30 mA	
Communication port protocol	Modbus serial with RS485 port(s)	
Mounting mode	Magnetic Snap-in	
Height	105 mm (standard) 95 mm (optional)	
Width	105 mm (standard) 95 mm (optional)	
Depth	33 mm (standard) 33 mm (optional)	
Relative humidity	1095 %, non-condensing (operation)	
order type	Mockup sample order	

Environment

Ambient air temperature for storage	060 °C
Ambient air temperature for	045 °C

Packing Units

PCE
1
5.5 cm
13.5 cm
18.5 cm
300.0 g
S03
20
30.0 cm
30.0 cm
40.0 cm
7.0 kg
P12
480
105.0 cm
80.0 cm
120.0 cm
183.0 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Under investigation

Use Again

○ Repack and remanufacture	
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins