

SpaceLogic Modbus 8 button Glass touch Panel with PIR sensor

SLGM08BUM

Main

Product name	Glass Touch Panels	
product type	Glass touch panel	
Colour tint	Front cover: champagne gold Front cover: silver Front cover: white	
	Front cover: black	

Complementary

Control button type	configurable touch button
[Us] rated supply voltage	24 V DC
Current consumption	<= 30 mA
Sensor type	PIR sensor
Communication port protocol	Modbus RTU with RS485 port(s), medium: twisted shielded pairs cable
Mounting mode	Snap-in
Height	95 mm
Width	95 mm
Depth	31.9 mm
Relative humidity	1090 %

Environment

Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	045 °C
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.15 cm
Package 1 Width	9.5 cm
Package 1 Length	9.5 cm
Package 1 Weight	201 g
Unit Type of Package 2	S03
Number of Units in Package 2	24

Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	7.294 kg
Unit Type of Package 3	P12
Number of Units in Package 3	576
Package 3 Height	10 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	129.926 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

0	Environmental	factoriat
~		100tpi iiit

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant with Exemptions	

Use Again

○ Repack and remanufacture		
End of life manual availability	End of Life Information	
Take-back	Yes	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	